

Application Profile









Application:
Vessel Name:
Vessel Construction:

Length (LWL/LOA):

Weight:

Engine Model: Engine Power: Drive Configuration: Gear Ratio and Model:

Gear & Throttle Control Type:

Cruise Speed: Top Speed: Propeller Size:

Commissioning Date:

Commercial Aluminium Catamaran

PT Transporter Aluminium 10.5 M / 11 M 14 tons

N9.430CR2 x 2 430hp @ 2300rpm Shaft – Remote v-drive

Twin Disc MG-5075-RV @ 1.72:1

Morse Mechanical

18 knots 24.5 knots

5 Blade, 23.5" dia x 29.2" pitch

08/05/19

Comments:

Repower with conversion from direct mount v-drive to remote mount v-drive. Greatly improving serviceability. Also, an increase in engine capacity from 7 litres to 9 litres for the same power. Providing much more torque and a true commercial rating.

Marine Diesel Pty Ltd provide this application profile for general information only. The data supplied is accurate only as to exact date, time and specifications set out in this report. Nanni and Marine Diesel Pty Ltd make no warranties as to the performance or fuel consumption of any boat equipped with Nanni engine/s as numerous factors affect actual performance of an engine/s.



Marine Diesel Pty Ltd Unit 21/29 Moreton Bay road Capalaba 4157

Phone: 07 3390 3633 Fax: 07 3390 3833

Email: Steve@marinediesel.net.au