


# QMS25M

25.5 kW max at 1500 rpm



### Engine base

- 4 strokes Diesel engine tested in all marine or industrial applications throughout the world.
- Engine block in cast iron type tunnel and timing gear.

### Injection and combustion system

- The Super Glow System comes as standard equipment to start the engine in cold temperatures.
- The E-TVCS injection system produces an ideal air/fuel mixture by creating three vortexes in the combustion chamber. The combustion efficiency is improved, resulting in low fuel consumption.

### Cooling system

- Cooling is ensured by heat exchange between coolant and seawater in an heat exchanger, or via a Keel Cooling system.
- Seawater pump with rubber impeller.

### Generator

- Delivering a continuous power of 23.2 kW and able to provide up to 25.5 kW.
- IP21 protection (additional level available on demand).

### Engine main features

- Kubota base Diesel engine
- 4 cylinders in line
- Closed cooling with heat exchanger
- Engine block in cast iron

### Generator main features

- Class H insulation
- 50 Hz
- Voltage accuracy of  $\pm 1.5\%$
- Radio interference suppression
- Electronic regulator

### Standard equipment

- Extension delivered by meter
- Closed cooling with heat exchanger
- Wet exhaust
- 12V Single-pole electrical system
- Safety shutdowns on low oil pressure and high coolant temperature
- Eco GE panel
- Rubber mounts
- Oil drain pump mounted on the engine

### Optional equipment

- Seawater hoses
- Seawater filter
- Siphon breaker
- Fuel feed system piping
- Exhaust system
- Fuel prefilter
- Keel Cooling
- Vertical dry exhaust
- 12V Double-pole electrical system
- Luxe GE panel (instead of Eco GE panel)
- Additional electric fuel feed pump

### Generator set ratings

Voltage (V)	Frequency (Hz)	Amperes (A)		Power * (kW)	
		max	cont.	max	cont.
230	50	46	41.9	25.5	23.2

Single-phased output with power factor  $\cos \phi = 1$

\*Continuous (COP) and max (PRP) power rating according to ISO 8528-1

### Weight and dimensions

	Without sound shield	With sound shield
Dry weight (kg)	378	550
Length (mm)	1304	1590
Width (mm)	636	750
Height (mm)	766	900

Find a Nanni dealer near you on:

[www.nannidiesel.com](http://www.nannidiesel.com)

Specifications are subject to change without prior notice. Non-binding document



# Generator set QMS25M

## Engine specifications

Engine base	Kubota
Cycle	4 strokes Diesel
Number of cylinders	4 in line
Displacement (cm <sup>3</sup> )	3318
Bore and stroke (mm)	98 x 110
Combustion system	Indirect (E-TVCS)
Rated rpm	1500
Intake	Natural

## Fuel system

Fuel injection pressure (bar)	140
Fuel injection pump	In line, Type Bosch MD mini
Fuel feed pump	Mechanical
Governor type	All speed mechanical

## Cooling system

Seawater pump	Neoprene rotor
Coolant pump type	Coaxial alternator driven
Coolant capacity (l)	12
Exhaust manifold	Fresh water cooled
Exhaust elbow.	Water injected
Max allowable back pressure (bar)	0.127
Max exhaust gas temperature (°C)	550

## Lubrication system

Oil pan capacity (l)	13
Oil type	API-CF mini 15W40
Oil filter	Full flow type filter
Lubrication system	Forced by trochoid pump

## Engine Electrical System

Engine alternator (V-A)	12 - 60
Battery recommended (Ah)	136
Starter motor (V-kW)	12 - 3

## Fuel consumption

Fuel consumption at full load (l/h)	8.2
-------------------------------------	-----


## Air requirements

Combustion air at 25°C (m <sup>3</sup> /h)	130
Flow for the evacuation of radiant heat (m <sup>3</sup> /h)	750

## Installation data

Exhaust connexion (mm)	60
Fuel connexion (mm)	8
Fuel pump - Max suction height (m)	0.5 (Standard pump) 1.8 (with add. electrical pump)
Sea Water pump connexion (mm)	32
Engine Operating Angle	15° continuous (30° maxi)


## Instrument panel



- Start and stop buttons
- Low oil pressure warning light
- Coolant temperature warning light
- Preheat warning light
- Battery charge warning light
- Oil pressure indicator \*
- Coolant temperature indicator \*


\*Only on Luxe GE panel

## Main components



1. Oil drain pump
2. Fuel feed pump
3. Fuel filter
4. Expansion tank
5. Seawater pump
6. Oil filter
7. Oil filler port
8. Exhaust elbow.

## Sound enclosure (optional)



1. Start & Stop buttons
2. Warning displays
3. Hourmeter
4. Emergency stop
5. Circuit breaker
6. Exhaust outlet
7. Seawater connection
8. Fuel connection
9. Power cable connection
10. Exhaust outlet
11. Battery connections